

















Indoor Flooring

Technical Specifications

Name	Standard	Symbol	Result
CE / DOP	EN 14041		CPR/AI/003
Usage Classification	EN 685 EN ISO 10874		23, 33, 42
Manufacturing Standard	EN 649 EN ISO 10582		Pass
Total Thickness	EN 428 EN ISO 24346		3,0 mm
Wear Layer Thickness	EN 429 EN ISO 24340		0,55 mm
Weight	EN 430 EN ISO 23997		7,800 g/m ²
Abrasion Resistance	EN 649 EN ISO 10582		Group T Type 1
Residual Indentation	EN 433 EN ISO 24343-1		≤ 0,1 mm
Dimension Stability	EN 434 EN ISO 23999		≤ 0,25 %
Dimensionsstabilitet / Curling	EN 434 EN ISO 23999		≤ 2 mm
Flexibility	EN 435 EN ISO 24344 method A		Pass
Slip Resistance	DIN 51130 EN 13893		Tick R9, Ceramic & Rustic R10 Class DS
Chemical Resistance	EN 423 EN ISO 26087		Excellent
Light Stability	EN ISO 105-B02		≥ 6
Flammability / Smoke Emissions	EN 13501-1		B _f -s1
Castor Chair Resistance (Type W)	EN 425 EN ISO 4918		Pass
Impact Sound Reduction	EN ISO 717-2		9 dB
Electrostatic Performance	ISO 6356 EN 1815		≤ 2 kV